

1) CONSTRUCTION:

CONDUCTOR:	22 AWG 7/30 STRANDED TINNED COPPER	NOM. DIA.	.030"
INSULATION:	SEMI-RIGID POLYVINYLCHLORIDE, .010" NOM. WALL THICKNESS		.050"
CABLE:	(3) INSULATED CONDUCTORS TWISTED TOGETHER TO FORM A CABLE CORE		.108"
JACKET:	POLYVINYLCHLORIDE, CHROME GRAY, .032" NOM. WALL THICKNESS	OVERALL CABLE DIAMETER	.172"

2) PHYSICAL PROPERTIES:

TEMPERATURE RATING, MAX.	60°C & 80°C
WT./M', NOM., NET.	17.9 LBS.

3) ELECTRICAL CHARACTERISTICS:

CAPACITANCE, MUTUAL	26.0 PF/FT.
DIELECTRIC WITHSTANDING, MIN VOLTAGE RATING, MAX.	1500V RMS
	300V
D.C. RESISTANCE, MAX. PER ASTM B286	16.7 OHMS/M'


4) AGENCY APPROVALS:
 (UL) NEC TYPE CM
 CSA AWM FT4
 UL STYLE 2464


5) APPLICATION:
 RS232 COMPUTER INTERCONNECT, CONTROL AND SOUND CABLE. RoHS COMPLIANT MATERIALS.

6) PRINT:
 QUABBIN 7121R (UL) TYPE CM 22 AWG OR AWM 2464 -- CSA LL51726 AWM I/II A/B 80C 300V FT4 -- RoHS --
(LOT DESIGNATOR)

7) COLOR CODE:
 1. BLACK
 2. RED
 3. GREEN

8) PACKAGING:
 TO BE PACKAGED AS PER QWC'S STANDARD PACKAGING



REVISION 03	DATE:	DRAWN S. ADDIE	08/12/97	
REVISED BY	B. M. DUCZYNSKI 10/20/05	CHECKED J. RIVERNIDER	08/12/97	
CHECKED	J. RIVERNIDER 10/20/05	CHECKED		
CHECKED		CUSTOMER APPROVAL:	DATE:	TITLE 3/C 22 AWG PVC/PVC CABLE --TYPE CM, STYLE 2464, CSA AWM FT4
				QUABBIN P/N 7121 1 OF 1