



58891
3 Cond



Rev:	Change:	By:	Date:

Construction		OD (In.)
1 Conductor:	22 AWG 19/34 Silver Plated Copper (SPC)	0.0295" nom
2 Dielectric:	Extruded Polytetrafluoroethylene (PTFE)	0.073" nom
Color:	Red, Yellow, White - <i>Black stripe</i>	
OD:		
3 Cable:	3 Primaries with Polyester Binder	0.159" nom
Drain:	22 AWG 19/34 Tin Plated Copper (TPC)	
4 Shield:	Aluminum/Polyester	0.162" nom
Coverage:	100%	
OD:		
5 Jacket:	Extruded ETFE	0.182" nom
Color:	Black	
Surface Print:	N/A	
OD:		

Physical Properties	
1 Weight per 1000':	TBD
2 Operating temperature range:	-65°C - 150°C
3 Voltage rating:	1000V
4 RoHS compliance:	Complies with RoHS (Directive 2002/95/EC)

Harbour Industries, Inc. 4744 Shelburne Rd, Shelburne, VT 05482 Ph: 802-985-3311 Fax: 802-985-0726 www.harbourind.com				
 Harbour INDUSTRIES <small>High Performance Wire & Cable</small>	Drawn By: <u>S. Wooster</u>	This drawing contains proprietary information and is issued in strict confidence and shall not be copied, reproduced, transmitted or disclosed to any third party either wholly or in part without prior written approval of Harbour Industries. All copies outside of the Harbour Industries CAD system are Uncontrolled.		
	Approved By: <u>M.T. Piner</u>			
	Date: <u>11/17/10</u>	Part Number:	Rev:	Sheet:
	Scale: <u>None</u>	TBD		1 of 1
	Drawing Name:	3 Cond. M22759/7-22 A/MDE ETFE		Drawing Number: 111810_1