

TO: INDUSTRIAL ELECTRIC
ATTN: JOHN KOHLER

SPECIFICATION SHEET

DATE: JULY 12, 2006

CUSTOMER: INDUSTRIAL ELECTRIC

REFERENCE: RFQ # 6000167369

DESCRIPTION: 3/C 22 AWG (19/34) TC, ETFE INSULATION,
36 AWG TPC BRAID, SANTOPRENE JKT.

PRIMARIES:

NUMBER: 3
AWG/STRAND: 22 AWG (19/34) TINNED COPPER
INSULATION THICKNESS: .006" NOMINAL WALL ETFE (TEFZEL)
PRIMARY O.D.: .042" (+ / - .003")
COLOR CODE: BLACK, WHITE, GREEN

FILLERS: NON - WICKING FOAMED POLYPROPYLENE AS REQUIRED

CABLE: (3) PRIMARIES & FILLERS

BRAID: 36 AWG TIN COPPER, 85% MINIMUM COVERAGE

SEPERATOR: MYLAR TAPE

JACKET: .030" NOMINAL WALL BLACK SANTOPRENE TPV 8261-87

FINAL O.D.: .175" NOMINAL **CABLE WEIGHT:** 24 LBS./MFT. NOMINAL

RATING: 300V, 105°C DRY, 75°C WET

PREPARED BY: RICH DEHAY