

Deca Cables Inc.

150 North Murray Street
PO Box 777
Trenton, ON
Canada
K8V 5W6

Telephone: (613) 392-3585

Fax: (613) 392-7908

ISO 9001 - 2000

PRODUCT DATA SHEET

PART NUMBER	73-103
DESCRIPTION	3 CONDUCTOR SHIELDED COMMUNICATION CABLE
CONDUCTOR	22 AWG SOFT TINNED COPPER
STRANDING	7 X 0.010"
CONDUCTOR DIAMETER	0.030"
RESISTANCE	16.2 OHMS/1000 FT
INSULATION	HD POLYETHYLENE
INSUL. COND. DIAMETER	0.061"
SHIELD	ALUM/MYLAR TAPE
DRAIN WIRE	24 AWG 7 X 0.008" SOFT TINNED COPPER
JACKET	PVC (80C)
JACKET THICKNESS	0.025"
FINISHED DIAMETER	0.194"
CAPACITANCE	20.4 PF/FT
IMPEDANCE	75.5 OHMS
CSA CERTIFIED	CMG AWM II
FLAME RATING	FT4

The material contained in this document is presented in good faith and believed to be reliable and accurate. However, because testing conditions may vary and material quality or information that may be provided in whole or part by others may be beyond our control, no warranty, expressed or implied, is given and Deca Cables Inc. can assume no liability for results obtained or damages incurred through the application of the data and tests presented.

Rev. 1
2004.02.12