



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: info@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

1-Oct-2014

Product Number : 5152203TFT4

RoHS

**O/A SH CABLE 3/C 22/7 AWG STC
SR-PVC Insulation
PVC FT-4 Jacket**

| | |
|---|----------------------------------|
| Conductor : 22 AWG 7x.0097 Tin Copper | |
| Total Cable Weight : 24 kg/km | Final Diameter : 0.150 inches |
| Insulation : SR-PVC | Jacket : PVC |
| Drain: 24 AWG 7 Strand STC Cond. | |
| DC Resistance 25°C: 17.3 Ohms / 1000 ft | Mutual Capacitance : 40.2 pF/ft |
| Impedance : 60 Ohms | Cond to Shield Cap. : 72.9 pF/ft |
| Velocity of Prop : 59 % | Inductance. : 1.5 mH/km |

Print Notes :

Standard Print : ECI ELECTROCOM CSA CMG 105°C LL61365 OR CSA AWM II A/B 105°C
600V FT-4 (UL) CMG E132883 105°C #22 AWG RoHS

(All of the above values are approximated to within +/- 10%)

5152203TFT4