

P.O. Box 276, Trenton, Ontario, K8V 5R5
 Voice: 888 - ELECTRO, Fax: 613 394 - 4101
 email: info@electrocables.com
 WWW.electrocables.com

Electro Cables Specification Sheet

Date: 26-Nov-09 Rev. 1

ECI Product#:

Product Description: Shielded 3/c-22/7 Tin Copper
 .015" PVC Insulation
 O/A Shield & 24/7 Tin Copper Drain
 .030" PVC Jacket 300V105°CFT-4 UL 2517

Conductor	# 22 AWG TINNED COPPER
Conductor Stranding	7 X .010
Nom Cond DC Resistance, ohms/1000 ft	16.6
Insulating Material Type	PVC
Insulation Wall Thickness, inches	0.015
Conductor Insulated O.D., inches	0.061
Overall Drain Wire Size	# 24 AWG TINNED COPPER
Final Twisted O.D., inches	0.133
Jacket Wall Thickness, inches	0.030
Jacket Material Type	PVC FT-4
Finished Cable O.D., inches	0.198
Total Cable Weight (kgs/km)	36.9
Cable CSA Approved	Yes
Cable UL Approved	Yes
RoHS Compliant	Yes

(All of the above values are approximated to within 10%)

773538

2203C OFS - 8EC1