

P.O. Box 276, Trenton, Ontario, K 8 V 5 R 5

Voice: 888 - ELECTRO, Fax: 613 394 - 4101

email: info@electrocables.com

www.electrocables.com

Electro Cables Specification Sheet

Date: 24-Mar-10 Rev. 1

ECI Product#: 5152203TFT4

Product Description: Shielded 3/c 22/7 Tinned Copper Conductor  
 .015" SR-PVC Insulation  
 O/A FOIL & 24/7 STC Drain  
 .030" PVC Jacket FT-4 105°C 600V UL 2517

|                                      |                        |
|--------------------------------------|------------------------|
| Conductor                            | # 22 AWG TINNED COPPER |
| Conductor Stranding                  | 7 X .010               |
| Nom Cond DC Resistance, ohms/1000 ft | 16.6                   |
| Insulating Material Type             | SR-PVC 105°C           |
| Insulation Wall Thickness, inches    | 0.015                  |
| Conductor Insulated O.D., inches     | 0.061                  |
| Overall Drain Wire Size              | # 24 AWG TINNED COPPER |
| Final Twisted O.D., inches           | 0.133                  |
| Jacket Wall Thickness, inches        | 0.030                  |
| Jacket Material Type                 | PVC FT-4               |
| Finished Cable O.D., inches          | 0.198                  |
| Total Cable Weight (kgs/km)          | 34.3                   |
| Cable CSA Approved                   | Yes                    |
| Cable UL Approved                    | Yes                    |
| RoHS Compliant                       | Yes                    |

(All of the above values are approximated to within 10%)

#774185