

National

Cable Specialists

Multi-Conductor 105C (Foil Shielded) CSA/FT4/UL

Conductor : Stranded tinned copper

Insulation : Colour coded semi-rigid PVC

Jacket : Grey PVC

Temperature : -20C to +105C

Shield : Overall 100% aluminum foil/polyester shield with stranded tinned copper drain wire.



Approvals : CSA certified CMG or CM to harmonized standard C22.2 No.214 and UL 444 (except larger than 16 AWG). Certified to standard C22.2 No.210.2-Type AWM. UL listed CL2 per standard UL13.

Applications : Data transmission, recording studios, broadcast sound systems, electronic & control circuits and signal applications in computers and industrial equipment.

* Click on color code for description of colors

Product Code	Cond. Size	# of Cond.	Cond. Strand	Drain Wire Size	Nom. Insul. Thickness (Inches)	Nom. Jacket Thickness (Inches)	Sugg. Working Voltage	Nom. O.D. (Inches)	Color Code	Ship. Weight Lbs/Mft
35DA2202	22	2	7 X 30	22	.010	.030	600	.167	Z	16
35DA2203	22	3	7 x 30	22	.010	.030	600	.167	Z	18
35DA2204	22	4	7 x 30	22	.010	.030	600	.188	Z	22
35DA2002	20	2	10 X 30	22	.012	.030	600	.180	Z	18
35DA2003	20	3	10 x 30	22	.012	.030	600	.200	Z	25
35DA2004	20	4	10 x 30	22	.012	.030	600	.216	Z	31
35DA1802	18	2	16 X 30	20	.015	.025	600	.218	Z	27
35DA1803	18	3	16 x 30	20	.015	.030	600	.236	Z	37
35DA1804	18	4	16 x 30	20	.015	.030	600	.261	Z	45
35DA1602	16	2	26 X 30	18	.018	.030	600	.265	Z	41
35DA1603	16	3	26 x 30	18	.018	.030	600	.281	Z	53
35DA1604	16	4	26 x 30	18	.018	.030	600	.307	Z	66
35DA1402	14	2	41 X 30	16	.020	.030	600	.302	Z	59
35DA1403	14	3	41 x 30	16	.020	.030	600	.320	Z	75
35DA1404	14	4	41 x 30	16	.020	.030	600	.350	Z	94
35DB2403	24	3	7 X 32	24	.010	.030	600	.160	1	15
35DB2404	24	4	7 X 32	24	.010	.030	600	.173	1	18
35DB2405	24	5	7 X 32	24	.010	.030	600	.190	1	21