



US North Central
 5001 S. Towne Drive
 New Berlin, WI 53151
 800-344-2323
www.IEWC.com

Specification

Issue Date: 2/13/2014

Issue: 1

Construction

Description:	4 Cond 22(7) TC Performance Cable				Diam. (In)																		
Component:	4 Conductors																						
Conductor:	22 7/30 TC to ASTM B 33-74				0.03"																		
Insulation:	0.01" PVC				0.05"																		
Color Code:	<table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th>Cond</th> <th>Color</th> <th>Cond</th> <th>Color</th> <th>Cond</th> <th>Color</th> <th>Cond</th> <th>Color</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Black</td> <td>2</td> <td>Brown</td> <td>3</td> <td>Red</td> <td>4</td> <td>Orange</td> </tr> </tbody> </table>					Cond	Color	Cond	Color	Cond	Color	Cond	Color	1	Black	2	Brown	3	Red	4	Orange		
Cond	Color	Cond	Color	Cond	Color	Cond	Color																
1	Black	2	Brown	3	Red	4	Orange																
Cable Assembly:	4 Conductors Bunched Cabled				0.121"																		
Fillers	Optional Fibrillated Polypropylene for roundness				0.121"																		
Tape:	Optional Non-Woven Separator Tape for Strip-Ability (our option)				0.124"																		
Jacket:	0.032"	PVC, Oil, Gas, Moisture and UV Resistant VW-1			0.188"																		
Jacket Color:	Gray				0.188"																		
Print:	E174416 RU AWM 2464 80C 300V and AWM 2661 105°300V VW-1 cUR AWM IA 80C 300V ROHS																						
Specifications:	<table border="0" style="width: 100%;"> <tr> <td style="width: 15%;">UL</td> <td style="width: 20%;">AWM - 2464</td> <td style="width: 10%;">80°C</td> <td style="width: 15%;">300 Volt</td> <td style="width: 10%;">VW-1</td> <td style="width: 30%;"></td> </tr> <tr> <td></td> <td>2661</td> <td>105°C</td> <td>300 Volt</td> <td>VW-1</td> <td></td> </tr> <tr> <td>Canadian cRU</td> <td>AWM</td> <td>80°C</td> <td>300 Volt</td> <td>FT-1</td> <td></td> </tr> </table> <p style="margin-left: 40px;">Jacket: Outdoor grade Agricultural Transportation Jacket Resistant to: Moisture, Flame, Oil, Fuel, UV</p>					UL	AWM - 2464	80°C	300 Volt	VW-1			2661	105°C	300 Volt	VW-1		Canadian cRU	AWM	80°C	300 Volt	FT-1	
UL	AWM - 2464	80°C	300 Volt	VW-1																			
	2661	105°C	300 Volt	VW-1																			
Canadian cRU	AWM	80°C	300 Volt	FT-1																			
Environmental Compliance	<p>EU Directive 2002/95/EC(RoHS): All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.</p> <p>REACH Regulation (EC 1907/2006): This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.</p> <p>California Prop 65: The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65.</p>																						