



QUALITY WIRE AND CABLE

Product Specification Sheet

1780 Birchwood Avenue
Des Plaines, Illinois, 60018
Ph: 847-299-9299 Fx: 847-299-9298
www.isotecwire.com
www.sheersoundcable.com

ISOTEC PART/QUOTE NUMBER: IP224BA7-52
CUSTOMER PART NUMBER:

DESCRIPTION: 22 AWG 4 CONDUCTORS 7/30 BARE COPPER, .008" SMOKEGUARD PVC, OVERALL .014" SMOKEGUARD PVC JACKET NATURAL CMP C(UL)US OR (UL) CL3P FT-6

CONDUCTOR/PAIR COUNT: 4 CONDUCTORS
GAUGE & STRANDING: 22 AWG 7/30 BC
D.C. RESISTANCE: 14.8 Ω/MFT
PRIMARY INSULATION TYPE: SGPVC
INSULATION THICKNESS: .008"
COLOR CODE: BLACK, WHITE, RED, GREEN
SHIELD: N/A
TAPE: N/A
DRAIN WIRE: N/A
CAP. COND TO COND.: 25 pF/ft
CAP. COND TO SHIELD: N/A
FOOTAGE MARKERS: ASCENDING & DESCENDING
PRINT LEGEND: IP224BA7-52 ISOTEC, INC. 22 AWG CMP C(UL)US OR (UL) CL3P FT-6
JACKET THICKNESS: .014"
JACKET COLOR: NATURAL
JACKET MATERIAL: SGPVC
RIPCORD: YES
NOMINAL O.D.: .132"
VOLTAGE RATING: 300V
TEMP. RATING: 60C
UL TYPE OR STYLE: CMP OR CL3P
PACKAGING: TBA
COPPER WEIGHT: 9.0 LBS/MFT
SHIPPING WEIGHT: 18 LBS/MFT

NOTES: Shipping Tolerance: +/- 10%
Length Tolerance: +/- 10%
Random/Odd Length Tolerance: May ship up to 15% of order total on random/odd lengths.
All wall thickness and diameter as well as electrical information is nominal.

ACCEPTANCE OF ABOVE DESIGN: _____ DATE: _____

Isotec makes every effort to provide accurate specifications. Printing errors are subject to correction.
Standard product specifications are subject to change without notice. Contact your Isotec sales person for current specifications.
Material will not be release to production until sign spec is confirm.