

Description: Four Conductor 22 AWG,
 Overall Tape Shield,
 Polyurethane Jacket

Create Date: 12/28/09

JM Part No: JM55918

Reference: W1214

Components Four 22 AWG, SRPVC Insulated Conductors	<u>Nom OD</u>
Conductor: 22 AWG, 7/30 bare copper	
Insulation: .010" nominal wall of SRPVC (see color code)	.050"

Overall Cable Construction

Cabling: 4 conductors cabled together
 Drain Wire: 22 AWG, 7/30 tinned copper
 Tape Shield: Aluminum/Mylar tape Foil In
 Jacket: .040" nominal wall of pressured Black Polyurethane .205" ± .010"

Print White Inkjet
 W1214 22/4 PUR E66440 RU AWM 21165 80C 300V VW-1 --- LL41103 CSA AWM I/II A/B 80C
 300V FT1

Color Code

- | | |
|----------|----------|
| 1. Red | 3. White |
| 2. Black | 4. Green |

Requirements

Temperature: 80°C
 Voltage: 300 V
 Min Bend Radius: 1.6" (8x OD)
 Cable Weight: 26 lbs/Mft
 Copper Weight: 11 lbs/Mft

Approvals:

AWM 21165
 CSA AWM I/II A/B FT1
 Materials are RoHS Compliant
 (2011/65/EU & EU 2015/863)

Written By:	rjc	12/28/09	Rev. 0	Initial Issue
Revised By:	rac/ka	06/04/18	Rev. 1	Revised to Change AWM Style from 20233 to 21165
Revised By:				