

Comtran Cable LLC 330A Turner Street South Attleboro, MA 02703-7714 (P) 508-399-7004 (F) 508-399-7360 www.ComtranCorp.com

Design Specification Part Number: 32785

DESCRIPTION:	22 AWG 4 conducto	Nom. O.D. (in.)	
CONSTRUCTION: Conductors: Insulation: Core Assembly: Shield:	 22 AWG 7 strand bare copper 0.0063" nominal wall SR PVC 4 conductors cabled together with a 1.75" nominal left hand lay Aluminum/polyester tape helically applied with the foil side out 24 AWG 7/32 tinned copper helically applied over the foil shield 0.014" nominal wall Chrome Gray PVC Parallel rip cord located under jacket 		.0415
Drain Wire: Jacket:			.131
COLOR CODE:	Black, White, Red, Green		
SPECIFICATIONS: UL 13, Power Limited Circuit Cable UL 1424 Power Limited Fire Alarm Circuit Cable UL 444, Communication Cables UL 1666, Riser Flame Test NEC Article 725, 760 and 800			
CERTIFICATIONS: UL Listed Type CL3R/FPLR C(UL)US Type CMR California State Fire Marshal Approved			
ELECTRICAL CHARACTERISTICS: Capacitance: 41 pF/ft nominal conductor to conductor @ 1 KHz			
SIGNATURE:DATE:			
DRAWING REV.	DATE DRWN. APP.	REMARKS	32785
2785 .07 0	8/21/06 2me RHW 5/11/05 2me RHW 1/24/03 2me RHW	Tri rate and add RoHS to print;Add ripcord Revised and redrawn Revised and redrawn	Page 1 of 1

