



Description: Four Conductor, 22 AWG
 Overall Foil Shield, and
 PVC Jacket

Date: 6/14/2013

JM Part Number: JM57205
Reference: IEWC-2204COFS-8

Components Four 22 AWG Insulated Conductors

Conductor: 22 AWG, 7/30 tinned copper

Insulation: .009" nominal wall of Semi-Rigid PVC (see color code) .048"

Cable Construction

Cabling: Four Conductors cabled together, No Fillers

Drain Wire: 22 AWG, 7/30 tinned copper

Shield: Aluminum-Mylar tape, Aluminum side IN, 100% coverage

Jacket: .020" nominal wall of Gray PVC .159"

Print
E138031 4/C 22 AWG SHIELDED 105C (UL) TYPE CM --- LL41103 CSA TYPE CMG 60C FT4

Color Code

1. Black	2. White	3. Red	4. Green
----------	----------	--------	----------

Requirements

Temperature: 105C (UL) 60C (CSA)	Approvals: UL Type CM CSA Type CMG, FT4 RoHS Compliant
Voltage: 600V (Non-UL)	

Written By:	rjc	6/14/2013	Rev. 0	Initial Issue
Revised By:	rjc	4/15/2014	Rev. 1	Added Shield Coverage, RoHS Compliancy, and Part Numbers
Revised By:				
Revised By:				