



Specification Sheet

TWC PART NUMBER: P20270.1/2280AB4M/CMP/CL3P

CONSTRUCTION : 22AWG 7/0096 BARE COPPER 4 CONDUCTORS OVERALL FOIL
COLOR CODE : CC#17: BLACK, RED, WHITE, GREEN
INSULATION : 0.008 Inch, LS PVC
SHIELD/DRAIN : OVERALL FOIL SHIELD, FOIL-OUT (BLUE IN). 24AWG 7/32 TC. DW
CAPACITANCE : 39.7 pF/ft Nom.
VEL OF PROP : 55%
IMPEDANCE : 47 OHMS
RESISTANCE : 17.5 OHMS D.C. PER 1000 FT @ 68 DEG. F
JACKET : WHITE, 0.014 Inch, LS PVC -- 0.137 Nom OD
CABLE WT : 17.1 Lb/1000ft Approx (EXCLUDING REEL OR BOX)
PRINT LEGEND : E118871 CMP/CL3P/FPLP 22AWG (UL) c(UL) MADE IN USA
UL : CMP/CL3P
MISC : MADE IN USA

* +/- 10% Manufacturing tolerance

* On non-standard product, customer agrees to accept all lengths manufactured

APPROVED BY

Tappan Wire & Cable Inc. provides information and specifications on an "as is" basis. Information in specifications described herein are subject to error and/or omission, and subject to change without notice. Although we make all efforts possible to ensure the accuracy and timeliness of the information, Tappan Wire & Cable, will not be held liable for any damages whatsoever, even if advised of the possibility of such damages, arising from the use, or inability to use, the information or specifications herein. Please refer to our "Website Use Policy", listed on our website, www.tappanwire.com, under the Sales Support Section for full details, or contact your Tappan Representative. This drawing may contain patented or proprietary information. It is the property of Tappan Wire and must not be used in any way detrimental to Tappan Wire. Acceptance by signature of this drawing will be considered as an agreement of and acceptance of the foregoing.