

770900

(3)



Multi/Cable
Corporation

THE WIRE PEOPLE

37 HORIZON DRIVE - TECHNOLOGY PARK
BRISTOL CT 06011-0797

www.multicable.com

7/10/2008

Industrial Electric Wire & Cable
5001 S. Tower Drive
New Berlin WI 53151

Attn: Karen Kusar
Re: Specification Sheet

Part Number:	LB022(19/T)-2PS
Conductor:	Twenty Two gauge stranded (19/34) tinned copper
No. of Conductors:	4-2 pairs
Primary Insulation:	.010" color coded premium grade PVC
Color Code:	Per Multi/Cable Color chart, or <u>customer request</u>
Construction:	Conductors twisted into pairs Pairs concentrically cabled on a common axis with an overall polyester binder to form a round and compact core.
Shielding:	100% overall aluminum/polyester foil facing in with 24 AWG stranded (7/32) tinned copper drain wire
Jackel:	.030" <u>Chrome</u> PVC with ripcord
Nominal OD:	.263" <u>Black O.S.</u>
Voltage:	300 Volt
Temperature:	-20°C to +80°C
Approvals:	Manufactured & Tagged per (UL) 2464- 80°C, 300 Volt.
Color Code:	Pair 1 Red, BLK Pair 2 Grn, wht

FOB Bristol CT
Shipping Tolerance +/- 10%

SERVING INDUSTRY'S NEEDS IN WIRE & CABLE

PHONE: 860-589-9035
FAX: 860-589-7520