

# Technical Data Sheet

## Aquaseal® Communication Cables

# WEST PENN WIRE

2833 West Chestnut Street  
Washington, PA 15301  
Toll Free: (800) 245-4964  
Fax: (724) 222-6420  
www.westpenn-wpw.com



<b>PART NUMBER:</b>	<b>AQC430</b>
<b>DESCRIPTION:</b>	2 Pair 22 Awg. Stranded tinned copper conductors, individually shielded with an Aquaseal tape and overall jacket.
<b>NEC RATING:</b>	CM or CL3, NEC Article 800 and 725
<b>APPROVALS:</b>	(UL) C(UL) Listed, (ETL)us Listed
<b>APPLICATION:</b>	Materials suitable for outdoor use, and indoor trays, allows a variety of uses for (Intercom, Security, Sound, Audio, Background music)

### Construction Parameters:

Conductor	22 AWG Tinned Copper
Stranding	7x30
Insulation Material	PVC
Insulation Thickness	0.010" Nom.
Number of Conductors	4 (2 Pair)
Shield	100% Aluminum Polyester Foil
Drain	Stranded Tinned Copper
Water-Blocking Tape	2 ply water swellable each pair
	Overall 2 Ply water swellable tape
Jacket Material	Sunlight/Moisture Resistance PVC
Jacket Thickness	0.025" Nom.
Overall Cable Diameter	0.380" Nom.
Approximate Cable Weight	29 Lbs/1M' Nom.
Flame Rating	UL 1685 Vertical Tray

### Electrical & Environmental Properties:

Temperature Rating	-20deg C to 60deg C
Operating Voltage	300 V RMS
Max.Capacitance Between Conductors @ 1 KHz	55 pf/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	99 pf/ft Nom.
DC Resistance per Conductor @ 20deg C	17 Ohms/1M' Nom.
Insulation Colors	Black, Red
Jacket Color	Gray
RoHS Compliant	Yes
TIA455-82B Water Infiltration Test Compliant	Yes
UL 444 & 13 Compliant	Yes

### Mechanical Properties:

Max. Recommended Pull Tension	58 lbs.
Min. Bend Radius (Install)	3.8"

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

Standard Lengths are 1000ft.  
The Jacket is sequentially footmarked.  
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.