

**ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION**

Part Number: S9802377
Page 1 of 1 Pages

Issue: 3
Issue Date: 5/5/2010
Effective Date: 5/5/2010

A. Construction

Diameters (In)

- 1) Component 1 2 X 1 PAIR
 - a) Conductor 22 (7/30) AWG TC
 - b) Insulation 0.027" Wall, Nom. Polyolefin 0.084
 - (1) Color Code Alpha Wire Company Color Code L
- | Pair | Color | Pair | Color | Pair | Color |
|------|------------|------|--------------|------|-------|
| 1 | WHITE-BLUE | 2 | WHITE-ORANGE | | |
- c) Pair 2/Cond Cabled Together
 - Individually Applied:
 - d) Shield: Alum/Mylar Tape, 25% Overlap, Min.
 - (1) Foil Direction Foil Facing Out
 - (2) Drain Wire 24 (7/32) AWG TC
 - e) Over Wrap: Clear Mylar Tape, 25% Overlap, Min.
 - 2) Cable Assembly 2 Components Cabled
 - a) Core Wrap Clear Mylar Tape, 25% Overlap, Min.
 - 3) Shield TC BRAID Shield, 95% Coverage, Min.
 - 4) Jacket 0.035" Wall, Nom., Polyethylene (PE) 0.450 (0.465 Max.)
 - a) Color(s) BLACK

B. Industry Approvals

- 1) EU Directive 2002/95/EC(RoHS):
All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.
- 2) REACH Regulation (EC 1907/2006):
This product may not contain any of the substances listed on the 13 January 2010 European Union's REACH Substance of Very High Concern (SVHC) candidate list in excess of 0.1% mass of the item.

C. Physical & Mechanical Properties

- 1) Temperature Range -20 to 75°C
- 2) Bend Radius 10X Cable Diameter
- 3) Pull Tension 29 Lbs, Maximum

D. Electrical Properties

(For Engineering purposes only)

- 1) Voltage Rating 300 V_{RMS}
- 2) Characteristic Impedance 110 Ω +/- 11
- 3) Mutual Capacitance 12.5 pf/ft @1 kHz, Nominal
- 4) Velocity of Propagation 73 %
- 5) Conductor DCR 17.22 Ω/1000ft @20°C, Nominal
- 6) NEXT 50Db/1000ft Min. .5 Mhz to 3.5 Mhz.

E. Other

- 1) Packaging
 - a) Bulk(Made-to-order)

This Design is custom, Made-To-Order & once accepted, the order is NON-CANCELLABLE & NON-RETURNABLE.

Accepted By:	Date:
Company:	Title:

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.