



ALPHA WIRE

Part Number: 15-1047
Page 1 of 1 Pages

Issue:
Issue Date: 6/9/2015

Cable Specification

Component 1 2 PAIR

Conductor: 22 (7/30) AWG TC

Insulation: 0.010" Wall, Nom. SR-PVC

Color Code: 4 SOLID COLORS/ 0 STRIPED/ 0 NUMBER CODED

Pair: 2/Cond Cabled Together

Final Assembly 2 Components

Core Wrap: NWP Tape, 25% Overlap, Min.

Shield: APA Foil Tape, 25% Overlap, Min.

Drain Wire: 22 (7/30) AWG TC

Braid: TC, 70% Coverage, Min.

Jacket: 0.032" Wall, Nom., PU

Jacket OD: 0.260"

Jacket Color: BLACK

Approvals

UL: AWM/STYLE 20668
VW-1

CSA: AWM I/II A/B
FT1

MIL: NONE

CE Compliant: YES

ROHS Compliant: YES

REACH Compliant: YES

Miscellaneous

Temperature: 90 C

Voltage: 300 V_{RMS}

Put Ups: 1000 FT PUTUP

Requested Quantity: 1000Ft.

Application Notes

color code needs to be white-green and red-black

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.