



Product Data Sheet



Part Number: C4064A

Revision: 2/12/2013

5C.22 AWG (7/30)TC PVC, PVC

COMMUNICATION & CONTROL CABLE

A. CONSTRUCTION

Conductor: #22 AWG (7/30) Tinned Copper
 Insulation: .010" Semi-Rigid Polyvinyl Chloride (SR-PVC)
 Cable Core: Cable 5/C @ 4.00" LHL
 Jacket: .032" Polyvinyl Chloride (PVC) jacket
 Print Legend: CAROL (R) 22 AWG -- C4064A -- 75C E105765-H CM (UL) C(UL) OR
 AWM STYLE 2464 -- CSA LL69381 CMG 60C -- ROHS -- MADE IN USA
 (DATE CODE) (SEQUENTIAL FOOTAGE)

DIAMETERS

.029" Nom
 .049" Nom
 .132" Nom
 .196" Nom

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG
UL Standard 1581	SUNLIGHT RESISTANT (720 HOUR)

C. ELECTRICAL PROPERTIES

Temperature:	-20C to +80C
Suggested Working Voltage:	300V Max
Conductor DCR:	16.9 Ohms/1000 ft @ 20°C (nom)
Mutual Capacitance:	24.5 pF/ft @ 1kHz (nom)

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	WHITE
3	RED
4	GREEN
5	BROWN

E. CUSTOMER APPROVAL

Signature: _____

Date: 2/13/13