



Product Data Sheet



Directive
2002/95/EC

Part Number: C5203 Beige

Revision Level: 0

Date: October 28, 2011

A. CONSTRUCTION

	5 Conductors 22 AWG Beige Cable	<u>DIAMETERS</u>
Conductor:	22 AWG (7/30) Tinned Copper	0.030"
Insulation:	General Purpose PVC Insulation .010"	0.050"
Cable:	5 Conductors	0.135"
Jacket:	Beige (Color Matched) PVC Jacket .032"	0.195"
Print Legend:	E194074 22 AWG (UL) TYPE CM 75C OR AWM 2576 80C 150V VW-1 LL109360 CSA TYPE CMG 75C FT4	

B. INDUSTRY APPROVALS

UL Standard 44	Type CMG
UL Subject 758	AWM Style 2576
CSA International	CMG FT-4

C. ELECTRICAL PROPERTIES

Temperature:	80C
Suggested Working Voltage:	150V – AWM 300V CMG
Conductor D.C. Resistance:	15.6 Ω at 20°C (Ohms/mft)
Mutual Capacitance:	34 pf / ft

D. COLOR CODE

1.	Black			
2.	White			
3.	Red			
4.	Green			
5.	Brown			

Written by:	Brian Hanlon	Rev. 0	Aug 11, 2011	Initial Drawing
Revised by:				
Revised by:				
Revised by:				