

5 WIRE 22 AWG(19 X .147mm TC UNILAY)

WIRE COLORS: BLUE, ORANGE, YELLOW, RED, BLACK

OUTER DIA OF CABLE 5.46±.13 mm
 SPIRAL SERVE SHIELD(90% MIN)
 TISSUE PAPER SEPARATOR

.229mm NOMINAL ENDOROFLEX INSULATION 105°C
 .178mm MINIMUM ENDOROFLEX INSULATION 300V
 OD 1.27 ± .05 mm, POLYESTER ELASTOMER

.762mm NOMINAL PRESSURED ENDOROFLEX JACKET
 .610mm MINIMUM PRESSURED ENDOROFLEX JACKET
 OIL AND WATER RESISTANT, ABRASION RESISTANT
 GRAY TPE

OPERATING TEMPERATURE RANGE
 -50°C TO 105°C

SUNLIGHT RESISTANT, NOT-PLENUM

MIN INSTALLED BENDING RADIUS 10X NOMINAL OD

CABLE IS NOT UL OR CSA RECOGNIZED

MANUFACTURER: NORTHWIRE INC.

NO	HT	HT
1E2722G	DRAWING	
1E013Y	CONFIDENTIALITY	
1E0198R	LETTERS	
1E0507D	IDENT	
1E2966B	IDENT	
1E0011	INTPR & TOL	

UNLESS OTHERWISE SPECIFIED	VERSION	PRIMARY
DIMENSIONS ARE IN mm	TYPE	SECONDARY
DIMENSIONS W/O TOL ARE BASIC		
THIRD ANGLE PROJECTION	SHEET	OF
	DWG CONTROL	M722

CATERPILLAR

THE INFORMATION HEREON IS THE PROPERTY OF CATERPILLAR INC. AND/OR ITS
 SUBSIDIARIES. WITHOUT WRITTEN PERMISSION IT IS LOANED, IS PROHIBITED
 OTHERS, AND ANY USE EXCEPT THAT FOR WHICH IT IS LOANED, IS PROHIBITED

CABLE	365-5032	VER	CHG
		-	00
			B