

Description: Five 22 AWG Conductors
 With Overall Foil Shield, Braid Shield,
 and PVC Jacket

Date: 6/3/2011

JM Part Number: JM56373

Reference: 2205CSS-8JM

Components Five 22 AWG Conductors

Conductor: 22 AWG, 19/34 tinned copper

Insulation: .016" nominal wall of PVC (see color code) .062"

Cable Construction

Cabling: Five conductors cabled together, fillers as needed

Foil Shield: Aluminum-Mylar tape, Aluminum side OUT

Drain Wire: 24 AWG, 7/32 tinned copper

Shield: 36 AWG tinned copper braid, 65% coverage

Separator: Tissue tape

Jacket: .035" nominal wall of Gray PVC .260"

Print

**E66440 5/C 22AWG SHIELDED 9\ AWM STYLE 2517 105C 300V --- LL41103 CSA
 AWM I/II A/B 105C 300V FT1 (+ Sequential Footage Markings)**

Color Code

1. Brown 2. Blue 3. White 4. Gray 5. Black

Requirements

Temperature: 105C
 Voltage: 300V

Approvals: UL AWM Style 2517
 CSA AWM, FT1

Written By:	rjc	6/3/2011	Rev. 0	Initial Issue
Revised By:	scs	6/9/2011	Rev. 1	Added JM and Reference Numbers
Revised By:	rjc	4/8/2014	Rev. 2	Add footage markings to print legend
Revised By:				