

---

**ALPHA WIRE COMPANY  
CDC PRODUCT SPECIFICATION**

---

Part Number: CDC9655  
Page 1 of 1 Pages

Issue: 1  
Issue Date: 8/10/2012

---

<b>A. Construction</b>		<u>Diameters</u>
1) Component 1	6 X 1 COND	
a) Conductor	22 (7/30) AWG TC	
b) Insulation	0.010" Wall, Nom. SR-PVC	
(1) Color Code	ALPHA WIRE COLOR CODE E	
2) Cable Assembly	6 Components	
a) Core Wrap	NWP Tape, 25% Overlap, Min.	
3) Shield:	AM Foil Tape, 25% Overlap, Min.	
a) Drain Wire	22 (7/30) AWG TC	
4) Jacket	0.032" Wall, Nom., PVC	0.223
a) Color	SLATE	
5) Packaging	1000FT PUTUP	
<b>B. Industry Approvals</b>		
1) UL	AWM/STYLE 2464 CM VW-1	
2) CSA	CMG FT4	
3) MIL	NONE	
4) CE Compliant	YES	
5) ROHS Compliant	YES	
<b>C. Physical &amp; Mechanical Properties</b>		
1) Temperature	105 C	
<b>D. Electrical Properties</b>		
1) Voltage Rating	300 V <sub>RMS</sub>	
<b>E. Other</b>		
1) Requested Quantity	15000Ft.	

**Application Notes**

Same as 5196C but no fillers or ripcord to speed up process on automatic stripping equipment--SR-PVC on insulation (not PVC as listed above)..similar to CDC9487 excpet 6 conductors

Note: cable will be a bit convoluted in appearance(not perfectly round).

Revision 1 8/10/2012

1. Remove rip cord but keep fillers to round out cable.

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR  
MANUFACTURING DEFECTS