

DGC DATA GUIDE CABLE

Electronic and Electrical Wire & Cable Products

232 Sherman Street Gardner, MA 01440
 Phone: 978-632-0900 Fax: 978-630-1872
 Visit us on our website: www.dataguidecable.com

**3 PAIR 22 AWG POLYOLEFIN INSULATED GENERAL PURPOSE INDIV. SHIELDED CABLE
 UL LISTED TYPE CM COMMUNICATION CABLES**

CONDUCTORS:
 - 22 AWG 7 Strands 30 AWG Tinned Annealed Copper in Accordance with ASTM B-3 and B-8

DIELECTRIC:
 - .010" Nominal Wall Thickness Polyolefin to Diameter of .050"

COLOR CODED:
 - As Indicated

PAIR ASSEMBLY:
 - Lay Length: 1-1/2" Nominal Hand
 - Shield: .0012" Nominal Thickness Aluminum/Polyester Tape Applied Helically, Foil Facing In

DRAIN:
 - 22 AWG 7/30 Tinned Copper under Foil Shield



CABLE ASSEMBLY:
 - Lay Length: 3" Nominal Left Hand
 - Filler: None Required

JACKET:
 - Material: Polyvinyl Chloride
 - Color: Chrome Gray
 - Wall Thickness: .032"
 - Finished Cable Diameter: .250"

CABLE MARKINGS:
 - Type: Ink Surface Printing on Jacket
 - Legend: "E123820 #22 (UL) TYPE CM 75C ALSO AWM 2919 LOW VOLTAGE COMPUTER CABLE -- LL91737 CSA TYPE CMH 75C"
 - Ink Color: Black

ELECTRICALS:
 - Cond. DC Resistance: 15.0 OHMS/1000'
 - Capacitance (Cond. to Shield): 55pf/ft

Customer Number	
D.G. Part Number	99D14-5
Prepared By:	KAM
Reviewed By:	WJD



COLOR CODE

PAIRS	COLOR
1	GREEN WITH BLACK/RED
2	YELLOW WITH BLACK/YELLOW
3	BLUE WITH BLACK/BLUE

AGENCY APPROVAL

- UL LISTED TYPE CM PER STANDARD SUBJECT 444 AND CSA TYPE CMH
 - RoHS

REVISION HISTORY

0	1/18/02	WD	INITIAL RELEASE
1	1/18/02	WD	ADD ELECTRICALS
2	7/22/14	WD	REFORMAT - RERELEASE