


# CONTINUOUS FLEX CABLES

## SD 200 Continuous flex halogen free polyurethane control data cable with extreme temperature range



Marking for SD 200 07742501:  
SAB BRÖCKSKES · D-VIERSEN · SD 200 25 x 0,14 mm² CE

SD 200 is a continuous flex multi-conductor cable with a temperature range of -40°C up to +90°C designed for high speed applications even in the most extreme conditions. The halogen free polyurethane jacket passes the stringent VDE test 0282 part 10 and HD 22.10 oil test and provides excellent resistance to chemicals and abrasion.

### Construction:

<b>Conductor:</b>	bare copper strands, extra fine wires
<b>Insulation:</b>	TPE 510
<b>Color code:</b>	with reference to DIN 47100
<b>Stranding:</b>	specially adjusted layering with non-woven tape over each layer
<b>Wrapping:</b>	non-woven tape
<b>Jacket material:</b>	PUR, TPU acc. to DIN VDE 0282 part 10 + HD 22.10 with mat surface
<b>Jacket color:</b>	gray

### Outstanding features:

- **labs uncritical**  
(labs = enamel moisturing interfering substances)
- **flexible at low temperatures**
- **halogen-free**
- **travel > 10 m is possible**
- **high abrasion resistance**
- **min. bending radius**
- **small outer diameter**

### Technical data:

<b>Peak operating voltage:</b>	max. 350 V acc. to DIN VDE
<b>Testing voltage U:</b>	1500 V acc. to DIN VDE 0472 part 509
<b>Min. bending radius</b> <i>continuous flexing:</i>	7.5 x O.D.
<b>Radiation resistance:</b>	5 x 10 <sup>6</sup> cJ/kg
<b>Temperature range</b> <i>static:</i> <i>flexing:</i>	-50/+90 °C -40/+90 °C
<b>Zero halogen:</b>	acc. to DIN VDE 0472 part 815 and IEC 60754-1
<b>Oil resistance:</b>	very good - TPU acc. to DIN VDE 0282 part 10 + HD 22.10
<b>Chem. resistance:</b>	good against acids, alkalines, solvents, hydraulic liquids etc.
<b>Continuous flexibility:</b>	very good
<b>Weather resistance:</b>	very good
<b>Absence of harmful substances:</b>	acc. to RoHS-guideline 2002/95/EG as well as GefStoffV appendix IV-no. 24, see page N/28

item no.	no. of conductors	nominal outer-Ø inch	outer-Ø mm	cable weight ≈ lbs/mft
<b>▶ 26 AWG (18/38) • 0.14 mm<sup>2</sup></b>				
07740201	2	0.126	3.2	7
07740301	3	0.130	3.3	9
07740401	4	0.142	3.6	10
07740501	5	0.150	3.8	12
07740701	7	0.173	4.4	16
07741001	10	0.201	5.1	20
07741201	12	0.205	5.2	23
07741401	14	0.217	5.5	26
07741801	18	0.236	6.0	32
07742501	25	0.280	7.1	42
07743201	32	0.299	7.6	52

item no.	no. of conductors	nominal outer-Ø inch	outer-Ø mm	cable weight ≈ lbs/mft
<b>▶ 24 AWG (32/38) • 0.25 mm<sup>2</sup></b>				
07740202	2	0.138	3.5	10
07740302	3	0.146	3.7	12
07740402	4	0.154	3.9	14
07740502	5	0.165	4.2	17
07740702	7	0.193	4.9	23
07741002	10	0.224	5.7	29
07741202	12	0.228	5.8	33
07741402	14	0.240	6.1	38
07741802	18	0.268	6.8	48
07742502	25	0.319	8.1	63
07743202	32	0.346	8.8	81

item no.	no. of conductors	nominal outer-Ø inch	outer-Ø mm	cable weight ≈ lbs/mft
<b>▶ 22 AWG (42/38) • 0.34 mm<sup>2</sup></b>				
07740203	2	0.146	3.7	11
07740303	3	0.154	3.9	14
07740403	4	0.165	4.2	17
07740503	5	0.177	4.5	20
07740703	7	0.205	5.2	28
07741003	10	0.240	6.1	35
07741203	12	0.248	6.3	40
07741403	14	0.260	6.6	46
07741803	18	0.287	7.3	58
07742503	25	0.350	8.9	80
07743203	32	0.374	9.5	100

Other dimensions and colors are possible on request.