

Comtran Cable LLC 330A Turner Street South Attleboro, MA 02703-7714 (P) 508-399-7004 (F) 508-399-7360 www.ComtranCorp.com

Design Specification

Part Number: 34956

DESCRIPTION: 22 AWG 8 conductor plenum communications cable Nom. O.D. (in.)

CONSTRUCTION:

Conductors: 22 AWG 7 strand bare copper

Insulation: 0.0063" nominal wall Comflex Plenum PVC .0415

Core Assembly: 8 conductors are cabled to a 2.5" L.H.L. and jacketed

Jacket: 0.014" nominal wall White Comflex Plenum PVC .165

Parallel ripcord located under jacket

COLOR CODE: Black, White, Red, Green, Brown, Blue, Orange, Yellow

SPECIFICATIONS: UL 13, Power Limited Circuit Cable

UL 1424 Power Limited Fire Alarm Cable

UL 444, Communication Cables

NFPA 262, Plenum Flame Test (UL 910)

NEC Article 725, 760 and 800

CERTIFICATIONS: UL Listed Type CL3P/FPLP

UL and cUL Listed Type CMP

California State Fire Marshal Approved

ELECTRICAL CHARACTERISTICS (@ 1 KHz):

Capacitance: 24 pF/ft nominal conductor to conductor

D.C. Resistance: $16.1 \Omega/\text{Kft nominal}$

SURFACE PRINT: E111272 (01-12345) 22 AWG CL3P/FPLP (UL) OR CMP C(UL)US RoHS

Sequential footage markers every 2 feet

| DRAWING | REV. | DATE | DRWN. | APP. | REMARKS | |
|---------|------|----------|-------|------|-------------------------------|-------------|
| 4956 | .08 | 02/20/08 | 2me | RHW | Add resistance | 34956 |
| 4956 | .07 | 06/22/06 | 2me | RHW | Add ripcord;Tri rate and RoHS | |
| 4956 | .06 | 02/11/05 | 2me | RHW | Revised and redrawn | Dogo 1 of 1 |
| 4956 | .05 | 09/29/04 | rhw | RHW | Revised primary OD | Page 1 of 1 |