



# Specification Sheet

## Lake Cable Part #: 228CST-DWC

**Description:** 22 AWG 8 conductor 7 strand tinned copper wire with PVC insulation, shielded, and PVC jacket for low-voltage electronic cable applications

### 1. Conductor

- 1.1.AWG Size & Stranding: 22 AWG 7 Strands Class B
- 1.2.Material: Annealed Tinned Copper
- 1.3.Conductor Count: 8 Conductors

### 2. Insulation

- 2.1.Material: Polyvinylchloride
- 2.2.Wall Thickness: 0.007"
- 2.3.Color Code: Black, Red, White, Green, Brown, Blue, Orange, Yellow

### 3. Assembly

- 3.1.Nominal Lay Length: 2.50" LHL (4.8 Tw/Ft)
- 3.2.Shield: Aluminum/Mylar - 100% Coverage
- 3.3.Drain Wire: 24 AWG 7 Strands Tinned Copper

### 4. Jacket

- 4.1.Material: Polyvinylchloride
- 4.2.Wall Thickness: 0.015"
- 4.3.Diameter: 0.202"
- 4.4.Color: Gray
- 4.5.Ripcord: Yes
- 4.6.Weight: 35 Lbs/Mft

### 5. Markings

- 5.1.Type: Cable permanently identified via surface inkjet print
- 5.2.Legend: DELCO WIRE & CABLE P/N-37908 E171197 22AWG 8C (UL) CMR C(UL)US OR (UL) CL3R 75°C SUN RES FT-4 "ROHS" MADE IN USA
- 5.3.Footage Markers: Yes

### 6. Standards

- 6.1.UL listed as type CL3R per UL standard 13 and as type CMR c(UL)us 75°C per UL standard 444
- 6.2.All materials used in the manufacture of this cable are RoHS compliant
- 6.3.Maximum Voltage: 300V
- 6.4.Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

\_\_\_\_\_  
Signature

\_\_\_\_\_  
Company

**ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION**