

P.O. Box 276, Trenton, Ontario, K 8 V 5 R 5
 Voice: 888 - ELECTRO, Fax: 613 394 - 4101
 email: info@electrocables.com
 www.electrocables.com

Electro Cables Specification Sheet

Date: 28-Jan-11 Rev. 1

ECI Product#: 5152208TFT4

Product Description: Shielded 8/c 22/7 Tinned Copper Conductor
 .010" SR-PVC Insulation
 O/A FOIL & 24/7 STC Drain
 .023" PVC Jacket FT-4 105°C 600V

Conductor	# 22 AWG TINNED COPPER
Conductor Stranding	7 X .010
Nom Cond DC Resistance, ohms/1000 ft	16.6
Insulating Material Type	SR-PVC 105°C
Insulation Wall Thickness, inches	0.010
Conductor Insulated O.D., inches	0.050
Overall Drain Wire Size	# 24 AWG TINNED COPPER
Final Twisted O.D., inches	0.165
Jacket Wall Thickness, inches	0.023
Jacket Material Type	PVC FT-4
Finished Cable O.D., inches	0.217
Total Cable Weight (kgs/km)	57.3
Cable CSA Approved	Yes
Cable UL Approved	Yes
RoHS Compliant	Yes

(All of the above values are approximated to within 10%)