

## COMPUTER CABLES

**Stranded Multi-Conductor  
Overall Aluminum Shield  
S-R Insulation -300 Volt**



CONSTRUCTION	
Conductor	- Stranded tinned copper multi-conductors
Insulation	- S-R PVC insulated with cabled conductors
Shield	- Aluminum polyester shield with stranded tinned copper drain Wire
Jacket	- Gray PVC Jacket

### Standards:

- UL 758
- UL 444
- NEC Article 800
- UL Listed CM
- UL Recognized AWM Style 2464 80C 300 Volts
- cUL Listed Type CMG
- California State Fire Marshal Approved

Part #	AWG	Conductors	Stranding	Insulation Thickness	Jacket Thickness	Nom. O.D.	Lbs./M'
D22204	22	4	7x2	.010"	.032"	.188"	26.3
D22206	22	6	7x2	.010"	.032"	.214"	35.3
D22208	22	8	7x2	.010"	.032"	.237"	43
D22210	22	10	7x2	.010"	.032"	.260"	51.1
D22212	22	12	7x2	.010"	.032"	.281"	54.2
D22215	22	15	7x2	.010"	.035"	.303"	69.4
D22220	22	20	7x2	.010"	.035"	.333"	87.5
D22225	22	25	7x2	.010"	.035"	.375"	101

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

COLOR CODE CHART	
Cond. #	Color
1	Black
2	White
3	Red
4	Green
5	Brown
6	Blue
7	Orange
8	Yellow
9	Purple
10	Gray
11	Pink
12	Tan