



Specification Sheet

Lake Cable Part #: S224PRCSP/X-IE

Description: 22 AWG 4 pair 7 strands bare copper wire, PP insulation, shielded, with an overall pressure extruded PVC Jacket.

- 1. Conductor**
 - 1.1. AWG Size & Stranding: 22 AWG 7 Strands Class B
 - 1.2. Material: Annealed Bare Copper
 - 1.3. Conductor Count: 4 Pairs
- 2. Insulation**
 - 2.1. Material: Polypropylene
 - 2.2. Wall Thickness: 0.008"
 - 2.3. Color Code: White x Green, Black x Red, White/Black x White/Red, White/Yellow x White x Green
- 3. Assembly**
 - 3.1. Pair Lay Length: 2.00" LHL (6.00 Tw/Ft)
 - 3.2. Cable Lay Length: 3.00" LHL (4.00 Tw/Ft)
 - 3.3. Shield: Aluminum/Mylar Tape - 100% Coverage
 - 3.4. Drain Wire: 24 AWG 7 Strand Tinned Copper
- 4. Jacket**
 - 4.1. Material: Pressure Extruded Polyvinylchloride
 - 4.2. Wall Thickness: 0.029"
 - 4.3. Diameter: 0.245" ± .015"
 - 4.4. Color: Black
 - 4.5. Ripcord: No
 - 4.6. Weight: 39 Lbs/Mft
- 5. Markings**
 - 5.1. Type: N/A
 - 5.2. Legend: N/A
 - 5.3. Footage Markers: N/A
- 6. Standards**
 - 6.1. All materials used in the manufacture of this cable are RoHS II and REACH compliant
 - 6.2. Maximum Operating Voltage: 300V
 - 6.3. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION