

Description: Four 22 AWG Twisted Pairs,
Overall Foil Shield and PVC Jacket

Date: 2/17/2011

JM Part Number: TBD

Reference : 9900-094

Components

Four 22 AWG Twisted Pairs

Conductor: 22 AWG, 7/30 tinned copper

Insulation: .010" nominal wall of Semi-Rigid PVC (see color code) .050"

Pair: Two conductors twisted together .100" (major axis)

Cable Construction

Cabling: Four twisted pairs cabled together

Drain Wire: 22 AWG, 7/30 tinned copper

Shield: Aluminum-Mylar tape, Aluminum side IN

Jacket: .063" nominal wall of Gray PVC .340"

Color Code

Pair 1: Black
Black/White

Pair 3: Red
Red/White

Pair 2: Orange
Orange/White

Pair 4: Yellow
Yellow/White

Print

**E138031 4/PR 22 AWG SHIELDED (UL) TYPE CM OR CL2 75C OR AWM 2343
80C --- LL41103 CSA AWM I/II A/B 80C 300V FT1**

Requirements

Temperature: 75C (CM/CL2)
80C (AWM)

Approvals: UL Type CM
UL Type CL2
UL AWM Style 2343
CSA AWM, FT1

Voltage: 300V

Written By:	rjc	2/17/2011	Rev. 0	
Revised By:				
Revised By:				
Revised By:				