

Honeywell

GENESIS SERIES CABLE

Low Voltage Cable
Part No. 1267

Description: 22 AWG 4Pr Sol EPS CM-CL2
Specifications: UL Standards 13, & 444; NEC Article 725
Assembly: Tubed jacket over individually shielded twisted-pairs

Construction:

Conductor: 22 AWG Solid Bare Copper
Insulation: Polypropylene
Insulation Thickness: 0.006" nom.
Insulation Colors: Pairs - Blk/Red, Blk/Wht, Blk/Grn, Blk/Blu
Insulation Diameter: 0.036 nom.
Lay Length: Twist -1.5" nom, Cable - 3.25" nom
Drain Wire: 22 AWG Solid Tinned Copper
Shield: 0.001" Thick Aluminum/Mylar

Jacket: PVC
Color: Gray
Jacket Thickness: 0.015" nom.
Outside Diameter: 0.199" nom.
Legend (Ink Print): HONEYWELL 22 AWG 4/PR (ETL) TYPE CM-CL2 - Sun. Res. (RoHS)- 3038058
W/O# XXXXXX-XXX XXXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Temperature Rating: -20 to 60 °C
Operating Voltage: 300 Volts max.
Capacitance: 30 pf/ft nom.
Impedance: 50 Ohms nom.
DC Resistance: 17.5 Ohms/M' at 20°C
Flame Rating: UL Vertical Tray