

AEROSPACE WIRE & CABLE, INC.
129-09 18TH AVENUE
COLLEGE POINT, NY 11356
(718) 358-2345
FAX (718) 358-2522

CABLE SPECIFICATIONS

- | | | | |
|------------------|---|-------------|--------------------|
| CUSTOMER : | | SHIP DATE : | |
| PART NUMBER : | 1984r | QUANTITY : | |
| 1) DESCRIPTION : | 9 Cond. Foil & Braid (Equal to B83559)
AWG 22/7x30 TC FEP/FEP red CMP | | |
| 2) CONDUCTOR : | AWG 22/7x30 Tinned Copper | O.D.= | .030" |
| 3) INSULATION : | FEP .006" wall | O.D.= | .040"-.044" |
| 4) COLOR CODE : | Black / White / Red / Green / Orange / Blue /
White-Black Stripe / Red-Black / Green-Black | | |
| 5) TWIST LAY : | 6" Lay on Cable | | |
| 6) SHIELD : | Aluminum / Mylar Shield with Aluminum side out | | |
| 7) BRAID : | Overall Tinned Copper Braid with 85% Coverage AWG 34 | | |
| 8) JACKET : | Red FEP .015" wall | O.D.= | .230" nom. |
| 9) MARKING : | E111036 TYPE CL2P-E130356 TYPE CMP 22AWG (UL),C(UL) | | |
| 10) CAPACITANCE: | 23 pF/foot nom. | | FEP/FEP |
| 11) WEIGHT : | 53 lbs / 1000 feet | | |
| 12) TEMPERATURE: | Mat'l Rated -80C to 200C | VOLTAGE: | UL 300V Power Ltd. |