



Manufacturers of High Temperature Wire & Cable



Aerospace Part#: 2210

PLENUM CABLE

DESCRIPTION

2 Pairs AWG 14/19x.015" TC
Overall Foil Shield FEP/FEP Gray CL2P

PHYSICAL PROPERTIES

Pairs		Insulation			
# Pairs	AWG	Material	Material	Wall	Finished OD
2	14/19x.015"	Tinned Copper	FEP	.007"	.084"

Outer Shield Material		Drain Wire		
Shield Type	Material	Coverage	AWG	Material
Overall Foil Shield	Alum / Mylar	100%	16/19x29	Tinned Copper

Outer Jacket Material		Cabling			
Jacket Material	Color	Wall	Overall O.D.	Lay	
FEP	Gray	.012"	.322" Nom.	2" Lay on Pair	4" Lay on Cable with Clear Mylar

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
UL Rated -80C to 200C	76.2 lbs/m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage
UL Rated 150V Power Ltd.

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs	
RoHS Compliant	YES
Suitability	Indoor, Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid
Applications	Audio, Control, Instrumentation Remote, Signaling, Power-limited systems
Flame Test	NFPA 262
NEC / (UL) Specification	CL2P

MISCELLANEOUS

Markings: E111036 TYPE CL2P 200C FEP/FEP 14 AWG (UL)
Color: Black/Red Black/White
Code:

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

* Specification subject to error and may change without notice