

Technical Data Sheet

Communication Cables



2833 West Chestnut Street
Washington, PA 15301
Toll Free: (800) 245-4964
Fax: (724) 222-6420
www.westpenn-wpw.com

PART NUMBER:	3273
DESCRIPTION:	22/12 Stranded bare copper conductors, shielded with an overall jacket.
NEC RATING:	CMR, NEC Article 800
APPROVALS:	(UL) C(UL) Listed or c(ETL)us Listed
APPLICATION:	Indoor for: Intercom, Security, Sound, Audio, Background Music, and Power Limited Control Circuits.

Construction Parameters:

Conductor	22 AWG Bare Copper
Stranding	7x30
Insulation Material	PVC
Insulation Thickness	0.010" Nom.
Number of Conductors	12
Shield	100% Aluminum Polyester Foil
Drain	Stranded Tinned Copper
Jacket Material	PVC
Jacket Thickness	0.015" Nom.
Overall Cable Diameter	0.255" Nom.
Approximate Cable Weight	52 Lbs/1M' Nom.
Flame Rating	UL 1666 Riser Flame Test

Electrical & Environmental Properties:

Temperature Rating	-20°C To +60°C
Operating Voltage	300 V RMS
Max.Capacitance Between Conductors @ 1 KHz	55 pf/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	99 pf/ft Nom.
DC Resistance per Conductor @ 20deg C	17 Ohms/1M' Nom.
Insulation Colors	Black, Red, White, Green, Brown, Blue, Orange, Yellow, Purple, Gray, Pink, Tan
Jacket Color	Gray
RoHS Compliant	--

Mechanical Properties:

Max. Recommended Pull Tension	123 Lbs.
Min. Bend Radius (Install)	2.5"

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire

Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.