



DECA CABLES INC.
150 North Murray Street
P.O. Box 777
Trenton, Ontario K8V 5W6
Canada

Telephone: (613) 392-3585

Fax: (613) 392-7908

ISO 9001 - 2000

PRODUCT DATA SHEET

PART NUMBER	73-196
DESCRIPTION	AWM SR/PVC 6 PAIR 22/1T IND SHIELDED FT4
CONDUCTOR	22 AWG TINNED COPPER
STRANDING	SOLID
CONDUCTOR DIAMETER	0.0253"
CONDUCTOR RESISTANCE	16.7 OHMS/1000FT
INSULATION	SR PVC
INSULATION THICKNESS	0.009"
INSUL. COND. DIAMETER	0.044"
CABLE ASSEMBLY	CONDUCTORS ARE PAIRED, INDIVIDUALLY SHIELDED AND TWISTED TOGETHER. (FOIL IN, DRAIN IN)
SHIELD	ALUMINUM/MYLAR
DRAIN WIRE	22 AWG 0.0253" SOLID TINNED COPPER
RIPCORDER	POLYESTER RIPCORDER UNDER JACKET
JACKET	PVC
JACKET THICKNESS	0.030"
FINISHED DIAMETER	0.327"
CSA CERTIFIED	CMG; 60C, 300V AWM II; 105C, 600V
UL RECOGNIZED	AWM STYLE 2464; 80C, 300V
FLAME RATING	FT4
ROHS	COMPLIANT

The material contained in this document is presented in good faith and believed to be reliable and accurate. However, because testing conditions may vary and material quality or information that may be provided in whole or part by others may be beyond our control, no warranty, expressed or implied, is given and Deca Cables Inc. can assume no liability for results obtained or damages incurred through the application of the data and tests presented.