



PRODUCT SPECIFICATION

March 1, 2013
Jenny Faber
IEWC

Part Number: L8SR022-15C-BLK

Conductor: 0.030" 22AWG 7(S) Tinned Copper

Insulation: 0.010" of 105°C Extruded Semi-Rigid Polyvinyl Chloride (SR-PVC)

Of Conductors: 15

Color Code:

1) Black	6) Blue	11) Pink
2) Red	7) Brown	12) Tan
3) White	8) Yellow	13) Red/Green
4) Green	9) Violet	14) Red/Yellow
5) Orange	10) Gray	15) Red/Black

Construction: 15 conductors concentrically cabled on a common axis with clear polyester binder tape to form a round and compact cable core. (Filler as necessary)

Jacket: 0.032" of Black 80°C Extruded Polyvinyl Chloride (PVC)

Nominal OD: 0.303"

Temp. Rating: 80°C

Voltage: 300 Volts

RoHS Compliant: Yes

(UL) Style: UL: AWM (300 V 80°C)

Shipping Tolerance: +/- 10%

Phone (860) 589-9035

www.multicable.com

Fax (860) 589-7520

This specification is proprietary information Owned by Multi/Cable Corporation and is submitted under a confidential relationship and may not be used or disclosed except for uses expressly granted by Multi/Cable. The information above is provided in good faith. It is believed to be accurate and represents the best information currently available to us. We make no warranty of merchantability, fitness for a particular purpose or of any other type, express or implied, with respect to products described or data or information provided, and we assume no liability resulting from such products, data or information. The user is required to comply with all laws and regulations relating to the purchase, use, storage and disposal of the products, and must be familiar with and follow generally accepted safe handling procedure. All dimensions herein are nominal.