

PROVO PART NUMBER
6719

**MULTI-CONDUCTOR • FOIL SHIELD • STRANDED TINNED COPPER
CONDUCTORS • CONDUCTORS TWISTED • PVC INSULATION • 100%
ALUMINUM FOIL SHIELD • STRANDED TINNED COPPER DRAIN WIRE
• PVC JACKET • -20°C +105°C**



SPEC CRITERIA	SPECIFICATION
AWG	22
STRANDING	7 x 30
NUMBER OF CONDUCTORS	19
DRAIN WIRE AWG	24
INSULATION TYPE	PVC
INSULATION THICKNESS	0.010
JACKET TYPE	PVC
JACKET THICKNESS	0.030
NOM. CABLE OD	0.319
VOLTAGE	600
TEMPERATURE	-20°C to +105°C
PUT-UP METERS	300 / 150
WEIGHT (LBS)	86 / 43
CSA	AWM, CMG, FT-4
UL	CMG, UL444
RoHS	COMPLIANT
FLAME TEST	FT-4
COLOUR CODE	1) Black 2) White 3) Red 4) Green 5) Orange 6) Blue 7) White w/Black 8) Red w/Black 9) Green w/Black 10) Orange w/Black 11) Blue w/Black 12) Black w/White 13) Red w/White 14) Green w/White 15) Blue w/White 16) Black w/Red 17) White w/Red 18) Orange w/Red 19) Blue w/Red