

DESCRIPTION: 40 CONDUCTOR 22 AWG PVC INSULATED CABLE,
UNSHIELDED WITH BLACK PVC JACKET
UL AND CSA RATED

CONDUCTOR: 22 AWG 7/30 TINNED ANNEALED COPPER IN ACCORDANCE
WITH ASTM B-3 AND B-8

DIELECTRIC: .010" NOMINAL WALL THICKNESS S-R PVC I/A/W UL AWM 1061
TO DIAMETER OF .050"

COLOR CODE: BELDEN CHART 2/2R

CABLE ASSEMBLY:

LAY LENGTH: 6" NOMINAL LEFT HAND DIRECTION(2 TWISTS/FOOT)
FILLER: FIBRALATED POLYPROPYLENE AS REQUIRED
BINDER: .001" NOMINAL THICKNESS POLYESTER TAPE

JACKET:

MATERIAL: THERMOPLASTIC PVC
COLOR: BLACK
WALL THICKNESS: .044" NOMINAL
FINISHED CABLE DIAMETER: .455" NOMINAL

CABLE IDENTIFICATION:

TYPE: SURFACE PRINT ON JACKET
INK COLOR: WHITE
LEGEND: "CMG 40C22 (UL) E123820 OR AWM 2576 or C(UL)
CMG ROHS"

NOTES:

UL TYPE CMG -20C TO 75C 300V(NOT MARKED)
UL AWM 2576 -20C TO 80C 150V
CSA TYPE CMG
CABLE WEIGHT: 150 lbs/1000'

DATA GUIDE

CABLE CORP.

ONE ERNRIC PLACE
GARDNER, MA. 01440
978-632-0900

TITLE
22 AWG 40/C BLK PVC/PVC CABLE

SCALE	P/N 09A6-3	REV
-------	---------------	-----

DATE 1/09	DRN. BY WJD	APP. BY
--------------	----------------	---------

REV	DESCRIPTION	DATE	APP.
3	REVISE PRINT REQUIREMENTS	2/27/09	
2	ADD LOW END TEMP@NOTES	1/21/09	
1	CHNGS PER CURTIS NOTES	1/19/09	
-	INITIAL RELEASE	1/7/09	