



GENERAL PRODUCT SPECIFICATION
 Phone 800-316-8877 Fax 978-368-1275
 www.jamesmonroewire.com

Description: Two Conductor, 24 AWG
 Overall ~~Black~~ PVC Jacket

Date: 1/23/2009

Gray

Part Number: JM45595
 Reference: W28302

Components Two 24 AWG Insulated Conductors

Conductor: 24 AWG; 16/36 bare copper

Insulation: .012" nominal wall of Semi-Rigid PVC .049"

Release Agent: Release agent applied to prevent bonding of conductors to jacket

Cable Construction

Cabling: Two conductors twisted together, no fillers

Jacket: .032" nominal wall of pressure extruded ~~Black~~ PVC .145" ± .010"

Gray

Color Code

1. White 2. Brown

Print

Jacket to be printed with Royal Blue ink as follows:

CANFIELD CONNECTOR W28302 24/2 E66440 RA AWM 2095 80C 300V
 VW-1 --- LL41103 CSA AWM III A/B 80C 300V FT1

Requirements

Temperature: 80C
 Voltage: 300V

Approvals: UL AWM Style 2095, VW-1
 CSA AWM, FT1

2402C-85M
 273105

APPROVED
 [Signature]
 1/26/09

Written By:	rjc	1/12/2009	Rev. 0	Initial Issue
Revised By:	scs	1/20/2009	Rev. 1	Added JM and Revised Reference Numbers
Revised By:				
Revised By:				