

**2/C #24 SHIELDED**

---

**CONDUCTORS:** #24 7/32 TC INSULATED WITH .010" SR PVC

**CABLING:** TWIST TWO (2) CONDUCTORS TOGETHER

**TAPE SHIELD:** WRAP WITH AN ALUMINUM/POLYESTER TAPE SHIELD, FOIL  
FACING OUT, 25% OVERLAP, 100% COVERAGE

**BRAID SHIELD:** TINNED COPPER BRAID SHIELD, 65% MIN COVERAGE

**JACKET:** .035" CHROME PVC

**NOM OD:** .185"

**PRINT IN WHITE:** E151405 24 AWG TYPE CM 105°C (UL)...AWM 2464...C(UL) 105°C 300V  
(1426) TYPE CMG ...CE...ROHS

**COLOR CODE:** 1) BLACK  
2) RED

**RATINGS:** ROHS COMPLIANT  
UV RESISTANT  
VW-1 (cUL TYPE CMG SURPASSES THIS RATING)  
-20 TO +80C  
300 VOLTS

---

I HAVE REVIEWED ABOVE SPECIFICATION AND IT CONFORMS TO ITEM ORDERED UNDER  
PO#

NOTE AND EXCEPTIONS HERE →

SIGNED: *John Smith*

DATED: 10/27/2010

2C#24FOIL-BS

---

10/25/2010

PAGE: 1 OF 1