

2 CONDUCTOR 24 AWG SHIELDED MINI-MAX AUDIO CABLE

29602
DRAWING NO.

Part No.	29602
CONDUCTOR	24 awg (7 x 0.0080") Tinned Copper O.D.: 0.024" (0.61 mm)
CONDUCTOR RESISTANCE	25.7 Ohms/Mft (84.3 Ohms/km)
INSULATION	0.009" (0.23 mm) Semi-Rigid Polyvinylchloride (SR-PVC) O.D.: 0.043" (1.09 mm)
COLOUR CODE	C1: Black C2: White
SHELD	Aluminum/Mylar Tape
DRAIN WIRE	24 awg (7 x 0.0080") Tinned Copper
RIPCORD	Polyester Ripcord Under Jacket
JACKET	0.015" (0.38 mm) Gray Polyvinylchloride (PVC)
OVERALL DIAMETER	0.125" (3.18mm)
WEIGHT	8.99 lbs/Mft (13.38 kgs/km)
IMPEDANCE	50 Ohms
CAPACITANCE	36.2 pF/ft (118.8 pF/m)
FLAME RATING	FT4
APPROVALS	CSA CMG 60°C, CSA AWM II A/B 105°C 600V FT4 UL CM

ALL DIMENSIONS NOMINAL UNLESS SPECIFIED AND SUBJECT TO CHANGE WITHOUT NOTICE

REVISION	APPD	DATE



DELCO WIRE AND CABLE LIMITED
1 Saramia Crescent Concord, Ontario L4K 3S6

DRWN	CM	DATE
		11/18/04
CHKD	AE	11/18/04
APPD	GS	4/12/04