



Deca Cables Inc.
 150 North Murray Street
 P.O. Box 777
 Trenton, Ontario K8V 5W6
 Canada

Website: www.decacables.com
 Telephone: (613) 392-3585
 Facsimile: (613) 392-7908
 Email: sales@decacables.com

ISO 9001:2008

PRODUCT DATA SHEET

Part No: 73-810

CONSTRUCTION SPECIFICATIONS

Description	Audio 2 Conductor 24 AWG Shielded
Conductor	24 AWG 7 Strand Tinned Copper - Concentric
Conductor Diameter	0.024"
Insulation Type	PVC
Insulation Thickness	0.009"
Cable Assembly	Conductors are cabled together with an overall shield and drain wire. (foil in, drain in)
Drain Wire	24 AWG 7 Strand Tinned Copper - Concentric
Overall Shielding Tape	Aluminum/mylar
Ripcord	Polyester Ripcord included under the cable jacket
Jacket	Flame Retardant PVC
Jacket Thickness	0.012" (minimum average)
Overall Cable Diameter	0.117"
Jacket Print	CSA CMG 24 AWG FT4 LL83251 ROHS (work order)

ELECTRICALS

Voltage	300V
Conductor Resistance	25.7 Ohms/Mft @20C

CERTIFICATIONS AND PHYSICAL PROPERTIES

CSA Certified	CSA C22.2 No. 214, Communications Cables
UL RECOGNIZED	None
Flame Test Rating	CSA FT4
Temperature Rating	60C
ROHS	Compliant
Cable Weight	13.33 kg/km
Copper Content	5.44 kg/km
Max Pull Tension	4 kgs
Min Bending Radius	1.00 inches (installed)
Min Installation Temp	-20C

Rev. 000

21-May-14