



**Description:** Two 24 AWG Conductors  
 With An Overall Foil Shield  
 and PVC Jacket

**Date:** 7/1/2013

**JM Part Number:** TBD

**Reference:** TBD

**Components** Two 24 AWG Insulated Conductors

Conductor: 24 AWG, 7/32 tinned copper

Insulation: .009" nominal wall of SR-PVC (see below for color code) .042"

**Cable Construction**

Cabling: Two Conductors

Drain Wire: 24 AWG, 7/32 tinned copper

Shield: Aluminum-Mylar tape, Aluminum side IN

Jacket: .020" nominal wall of Gray PVC .127"

**Print**  
**E138031 2/C 22 AWG SHIELDED 105C (UL) TYPE CM - - - LL41103 CSA TYPE CMG 60C FT4**

**Color Code**  
 1. Black                      2. White

**Requirements**

Temperature: 105C (UL)                      Approvals: UL Type CM  
 60C (CSA)    CSA Type CMG, FT4

Voltage: 600V (Non-UL)

|             |     |          |        |               |
|-------------|-----|----------|--------|---------------|
| Written By: | rjc | 7/1/2013 | Rev. 0 | Initial Issue |
| Revised By: |     |          |        |               |
| Revised By: |     |          |        |               |
| Revised By: |     |          |        |               |