



[Home](#) | [Contact](#) | [P/N Index](#)

[PRODUCTS](#)

[COMPANY](#)

[ORDER](#)

[NEWS](#)

[TECHNICAL](#)

Pro A/V & Broadcast Cable

ANALOG AUDIO CABLE

[PRODUCTS](#) / [PRO-AUDIO, VIDEO & DATA CABLE](#) / [ANALOG AUDIO CABLE](#) / Microphone Cable: Thin Profile

Microphone Cable: Thin Profile



Thin profile and easy-to-terminate microphone cable for applications where reduced size and weight are required. The reduced diameter, matte PVC jacket, and tight-angle braid shield make MP1022 both extremely flexible and easy to handle. Ideal for mobile production trucks, multi-pin to XLR breakout cables, bantam or longframe patchcords, and short distance balanced mic or line level equipment interconnect.

FEATURES & BENEFITS

- Thin Profile
- Light Weight
- Low Attenuation
- Extra-flexible
- Polyethylene Dielectric
- Full Copper Braid Shield
- Drain Wire for Quick Shield Termination
- Matte PVC Flexible Master Jacket

APPLICATIONS

- Microphone or Line Level Balanced Analog Audio
- Portable Microphone Cables
- Balanced Equipment Interconnect
- Longframe or Bantam Patchcords

Mechanical Specifications

Part #	# of Pairs	Nominal OD	Conductors	Insulation (type, wall thick)/ Color Code	Shield	Drain Wire	Jacket	Jacket Colors	Approx. Weight
MP1022	1	.194"	24 AWG (41x40) Stranded TC	PE, .013" / White & Black	95% TC Braid	22 AWG (41x40) Stranded TC	Flexible Matte PVC	Black, Red, Green, Blue	25 lbs/Mft

Electrical Specifications

Capacitance	Cond. DCR	Drain DCR
20 pF/ft between conductors, 37 pF/ft between one conductor and other tied to shield	25.6 Ω/Mft	25.6 Ω/Mft

[Back](#)

Toll Free: 800-966-0069 FAX: 847-795-8770

©2010. General Cable Technologies Corporation, Highland Heights, KY 41076. All rights reserved.

