

P.O. Box 276, Trenton, Ontario, K 8 V 5 R 5
 Voice: 888 - ELECTRO, Fax: 613 394 - 4101
 email: info@electrocables.com
 www.electrocables.com

Electro Cables Specification Sheet

Date: 01-Feb-13 Rev. 1

ECI Product#: 5152451TFT4

Product Description: Shielded 1 pr. or 2/c 24/7 Tinned Copper Conductor
 .010" SR-PVC Insulation
 O/A Shield & 24/7 STC Drain Wire
 .020" PVC Jacket FT-4 105°C 600V

Conductor	# 24 AWG TINNED COPPER
Conductor Stranding	7 X .008
Nom Cond DC Resistance, ohms/1000 ft	25.5
Insulating Material Type	SR-PVC 105°C
Insulation Wall Thickness, inches	0.010
Conductor Insulated O.D., inches	0.044
Pairing O.D., inches	0.088
Overall Drain Wire Size	# 24 AWG TINNED COPPER
Final Twisted O.D., inches	0.090
Jacket Wall Thickness , inches	0.020
Jacket Material Type	PVC FT-4
Finished Cable O.D. , inches	0.135
Total Cable Weight (kgs/km)	20.4
Cable CSA Approved	Yes
Cable UL Approved	Yes
RoHS Compliant	Yes

(All of the above values are approximated to within 10%)