



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
 www.huesonwire.com

Issue Date: 4/8/2015

Issue: 1

Construction

Description:	1/PR 24 AWG mPPE/TPV OAFS	Diam. (In)
Component:	2 Conductors (1 Pair)	
Conductor:	24 AWG 7/32 Bare Copper (0,22mm) to ASTM B-8	0.024"
Insulation:	0.010" mPPE Automotive Grade	0.044"
Color Code:	Black + Red (or customer option)	0.044"
Cable		
Assembly:	1 Pair Twisted with overall foil shield and drain wire	0.088"
Braid:	Tinned Copper Braid Shield	0.091"
Jacket:	0.03" Santoprene TPV	0.151"
Jacket Color:	Black	0.151"

Print: No print required

Specifications:

Inner conductors built to ISO-6722 Class B

Transportation Grade Jacket, TPV resistant to UV, oil, fuel, moisture

Environmental Compliance

EU Directive 2011/65/EC(RoHS):
 All materials used in the manufacture of this part are in compliance with EU Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.

REACH Regulation (EC 1907/2006):
 This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.

California Prop 65:
 The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65.