



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 2/14/2017
Issue: 1

Construction C5626

Description: 3/C 24 16/36BC SR-PVC/PVC		Diam. (In)
Component:	3 Conductors	
Conductor:	24 16/36 Bare Copper	0.026"
Insulation:	0.0115" Semi-Ridgid PVC	0.049"
Color Code:	Black, Brown, Blue	0.049"
Cable Assembly:	3 Conductors Bunched Cabled Apply release agent	0.106"
Jacket:	0.025" Gray PVC Jacket Matte Finish	0.145"
Jacket Color:	Gray	0.145"

Print: W1026 24/3 E174416 RU AWM STYLE 2095 80C 300V VW-1 - - cRU AWM I/II A/B 80°C 300V
Royal Blue FT-1

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>	
UL	AWM-2095	80°C	300	VW-1	
Canadian cRU	AWM	80°C	300	FT-1	I/II A/B

Environmental Compliance

- EU Directive 2011/65/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65:

Min bend Radius 8 X CableDiameter
 Canfield #W1026
 IEWC P/N 2403C-8JM



Hueson Wire
38 Sutton Street
Northbridge, MA 01534
508-234-6372
bhanlon@huesonwire.com

Issue Date: 2/14/2017
Issue: 1

Drawing/Rotation:

