Hue: Wire & Ca	SON		Hueson Wire 38 Sutton Street Northbridge, MA 015 508-234-6372 www.huesonwire.c	
	one	Specificatio	n Issue Date:	5/29/2014
		-	Issue:	4
Construction	1			
Description:	3 Cond 24 (19	9) PVC/TPU Cable Hach C5187		Diam. (In)
Component:	3 Conductors			
Conductor:	24 AWG 19/36	6 Tinned Copper to ASTM B-8	Unilay	0.024"
Insulation:	0.023"	Premium Grade PVC		0.070"
Color Code:	Color	Color Color 2 White 3 Blue	Color Color	
Assembly:	3 Conductors	Bunched Cabled		0.151"
Drain Wire:	24 19/36 TC			0.151"
Braid:	Tinned Coppe	r Braid Shield 8 Ends of 36 AWG	90% Min Coverage	0.172"
Tape:		eparator Tape for Strip-Ability		0.175"
Jacket:	0.050"	Halogen Free Polyurethane (Pre	essure Extruded)	0.275"
Jacket Color:	Yellow			0.275"
Print: No Print Required				
Specifications:	87 Shore A Du	urometer		
	300 Volt	$\mathcal{T}08$		
Environmental Compliance EU Directive 2011/65/EU (RoHS):` All materials used in the manufacture of this part are in compliance with EU Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.				
REACH Regulation (EC 1907/2006):				
This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. California Prop 65:				
The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65.				

