

P.O. Box 276, Trenton, Ontario, K8V 5R5  
 Voice: 888 - ELECTRO, Fax: 613 394 - 4101  
 email: info@electrocables.com  
 www.electrocables.com

Electro Cables Specification Sheet

Date: 26-May-11 Rev. 1

ECI Product#: 5152403TFT4

Product Description: Shielded 3/c 24/7 Tinned Copper Conductor  
 .010" SR-PVC Insulation  
 O/A Shield & 24/7 STC Drain Wire  
 .020" PVC Jacket FT-4 105°C 600V

Conductor	# 24 AWG TINNED COPPER
Conductor Stranding	7 X .008
Nom Cond DC Resistance, ohms/1000 ft	25.5
Insulating Material Type	SR-PVC 105°C
Insulation Wall Thickness, inches	0.010
Conductor Insulated O.D., inches	0.044
Overall Drain Wire Size	# 24 AWG TINNED COPPER
Final Twisted O.D., inches	0.097
Jacket Wall Thickness, inches	0.020
Jacket Material Type	PVC FT-4
Finished Cable O.D., inches	0.142
Total Cable Weight (kgs/km)	24.1
Cable CSA Approved	Yes
Cable UL Approved	Yes
RoHS Compliant	Yes

(All of the above values are approximated to within 10%)